


**Luminaire**

# Styrk

**86-200D-20GGE/840, B**


The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

**Technical drawing**


|                              |                                 |
|------------------------------|---------------------------------|
| Type of installation         | Surface                         |
| Light distribution           | Direct                          |
| Luminaire shape              | Linear                          |
| Colour of the luminaires     | Black                           |
| Material                     | Aluminium                       |
| Lifetime                     | L90/B50 50 000 hours            |
| Warranty                     | 5 years                         |
| Description of luminaires    | Luminaire surface               |
| Dimensions                   | 1127 mm × 56 mm × 58 mm         |
| Light source                 | LED MODUL                       |
| Type of optical system       | Asymmetric reflector            |
| Luminous flux                | 2750 lm ± 10 %                  |
| Colour Temperature           | 4000 K cool white               |
| Luminous efficacy            | 124 lm/W                        |
| MacAdam Light source         | 3                               |
| Colour rendering index       | 80                              |
| Luminaire power input        | 22.1 W ± 10 %                   |
| Connection of the luminaires | Electronic ballast non-dimmable |
| Electrical voltage           | 220-240V                        |
| Frequency                    | 50/60Hz                         |

 IP 54

## Downloads

Installation instructions



Photos

