



## Luminaire

# Styrk

86-500D-40GHE/830, B



The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

## Technical drawing



|                              |                                 |
|------------------------------|---------------------------------|
| Type of installation         | Suspended                       |
| Light distribution           | Direct                          |
| Luminaire shape              | Linear                          |
| Colour of the luminaires     | Black                           |
| Material                     | Aluminium                       |
| Lifetime                     | L80/B10 70 000 hours            |
| Warranty                     | 5 years                         |
| Description of luminaires    | Luminaire suspended             |
| Dimensions                   | 2249 mm × 56 mm × 58 mm         |
| Light source                 | LED MODUL                       |
| Type of optical system       | Asymmetric reflector            |
| Luminous flux                | 8630 lm ± 10 %                  |
| Colour Temperature           | 3000 K warm white               |
| Luminous efficacy            | 118 lm/W                        |
| MacAdam Light source         | 3                               |
| Colour rendering index       | 80                              |
| Luminaire power input        | 73 W ± 10 %                     |
| Connection of the luminaires | Electronic ballast non-dimmable |
| Electrical voltage           | 220-240V                        |
| Frequency                    | 50/60Hz                         |

 IP 54

# Curve



## Downloads

Installation instructions



Photos

