



## Luminaire

# Styrk

86-500Q-40GGM3/840, S



The focus on performance is ever greater. No wonder nowadays - that's why we come up with Styrk technical luminaires. They meet strict criteria and have a wide range of applications. They stand out with a luminous flux of 5000 lm/m and a specific luminous flux of 145 lm/w while meeting IP54. Equipped with opal, microprism or PMA, these pendant luminaires can also be easily connected via a connector system. In addition, they can withstand high ambient temperatures of up to 40° C. They are suitable for business centres, data centres and large production halls.

## Technical drawing



|                              |   |
|------------------------------|---|
| Type of installation         | Suspended   |
| Light distribution           | Direct  |
| Luminaire shape              | Linear  |
| Colour of the luminaires     | Silver  |
| Material                     | Aluminium   |
| Lifetime                     | L90/B50 50 000 hours                              |
| Warranty                     | 5 years   |
| Description of luminaires    | Luminaire suspended                               |
| Dimensions                   | 2249 mm × 56 mm × 58 mm                           |
| Light source                 | LED MODUL   |
| Type of optical system       | Adjustable beam angle                             |
| Luminous flux                | 6330 lm ± 10 %                                    |
| Colour Temperature           | 4000 K cool white                                 |
| Luminous efficacy            | 151 lm/W  |
| MacAdam Light source         | 3   |
| Colour rendering index       | 80  |
| Luminaire power input        | 41.8 W ± 10 %                                     |
| Connection of the luminaires | Electronic ballast non-dimmable with 3h emergency |
| Electrical voltage           | 220-240V  |
| Frequency                    | 50/60Hz   |

 IP 54

# Curve



## Downloads

Installation instructions



Photos

