


**Leuchte**

# Flumo60-S

**228S-XXXI-XXGXE/840, W**


Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Typ der Montage	Aufbauleuchten, Pendelleuchten
-----------------	--------------------------------

Typ der Ausstrahlung	Direkte
----------------------	---------

Form der Leuchte	Andere Leuchtenform
------------------	---------------------

Farbe der Leuchte	Weiss
-------------------	-------

Material	Aluminium
----------	-----------

Lebensdauer	L80/B20 50 000 Stunden
-------------	------------------------

Garantie	60 Monate
----------	-----------

Beschreibung der Leuchte	Aufbau-/Pendelleuchte
--------------------------	-----------------------

Produktbeschreibung	Die Arche Rxxx - Y°
---------------------	---------------------

Abmessungen	0 mm × 60 mm × 65 mm
-------------	----------------------

Art der Optik	Mikroprismatische Optik
---------------	-------------------------

Lichtstrom	455 lm - 4020 lm ± 10 %
------------	-------------------------

Farbtemperatur	4000 K Kalt weiss
----------------	-------------------

Leuchtwirkungsgrad	95 lm/W
--------------------	---------

MacAdam	3
---------	---

Lichtquelle	
-------------	--

Farbwiedergabeindex	80
---------------------	----

UGR max. X=4H	99
---------------	----

Y=8H, ρ=70,50,20	
------------------	--

Leistungsaufnahme	4.8 W - 43 W ± 10 %
-------------------	---------------------

Anschluss der Leuchte	EVG nicht dimmbar
-----------------------	-------------------

Elektrische Spannung	220-240V
----------------------	----------

Frequenz	50/60Hz
----------	---------

⊕ CE IP 20

**Zum Herunterladen**

Montageanleitung



Fotografie

