



## Leuchte

# Flumo60-S

228S-XXXX-XXGXE/830, W



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Typ der Montage      Aufbauleuchten, Pendelleuchten

Typ der Ausstrahlung      Direkte

Form der Leuchte      Andere Leuchtenform

Farbe der Leuchte      Weiss

Material      Aluminium

Lebensdauer      L80/B20 50 000 Stunden

Garantie      60 Monate

Beschreibung der Leuchte      Aufbau-/Pendelleuchte

Produktbeschreibung      Die Arche Rxxx - Y°

Abmessungen      0 mm × 60 mm × 65 mm

Art der Optik      Opaler Diffusor

Lichtstrom      340 lm - 4550 lm ± 10 %

Farbtemperatur      3000 K Warm weiss

Leuchtwirkungsgrad      89 lm/W

MacAdam      3

Lichtquelle

Farbwiedergabeindex      80

UGR max. X=4H      99

Y=8H, ρ=70,50,20

Leistungsaufnahme      3.8 W - 43 W ± 10 %

Anschluss der Leuchte      EVG nicht dimmbar

Elektrische Spannung      220-240V

Frequenz      50/60Hz

 **CE** IP 20

**Zum Herunterladen**

Montageanleitung



Fotografie

