



Leuchte

Flumo60-S

228S-XXXX-XXGXE/840, B



Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Typ der Montage Aufbauleuchten, Pendelleuchten

Typ der Ausstrahlung Direkte

Form der Leuchte Andere Leuchtenform

Farbe der Leuchte Schwarz

Material Aluminium

Lebensdauer L80/B20 50 000 Stunden

Garantie 60 Monate

Beschreibung der Leuchte Aufbau-/Pendelleuchte

Produktbeschreibung Die Arche Rxxx - Y°

Abmessungen 0 mm × 60 mm × 65 mm

Art der Optik Opaler Diffusor

Lichtstrom 435 lm - 4780 lm ± 10 %

Farbtemperatur 4000 K Kalt weiss

Leuchtwirkungsgrad 114 lm/W

MacAdam 3

Lichtquelle

Farbwiedergabeindex 80

UGR max. X=4H 99

Y=8H, ρ=70,50,20

Leistungsaufnahme 3.8 W - 43 W ± 10 %

Anschluss der Leuchte EVG nicht dimmbar

Elektrische Spannung 220-240V

Frequenz 50/60Hz

  IP 20

Zum Herunterladen

Montageanleitung



Fotografie

