





Family

Flumo60-S

Based on the great success of Flumo100-S, we decided to create its little brother called Flumo60-S with a narrower profile of 60 mm for a more decent look. It is a linear aluminium profile that winds along the ceiling in a perfect curve and navigates you through the space. The Flumo60-S luminaires are available in both pendant and surface versions. Thanks to a wide range of radii and lengths, the luminaire can be used to create countless shapes of light objects. If we add the possibility of direct or direct-indirect distribution of light and two types of optical systems, we get a universal tool for illuminating social, public or commercial spaces.

Type of installation	Surface, Suspended
Light distribution	Direct
Colour of the luminaires	Black, Silver, White
Colour Temperature	3000 K warm white, 4000 K cool white
Material	Aluminium
Connection of the luminaires	ON/OFF
Lifetime	L80/B20 0 hours

Luminaire family variants Flumo60-S




Flumo60-S




<div><div><div>580</div><div>860</div><div>1140</div><div>1420</div><div>1700</div><div>1980</div><div>2260</div></div><div><div>A-A:</div><div><div><div>65</div><div>60</div></div></div><div><div>A</div><div>A</div></div></div></div>	<div><div>Assembly</div><div><div><div><div></div><div></div></div></div></div></div>	<div><div>Light distribution</div><div><div><div></div></div></div></div>	
	<div><div>Energy class</div><div><div>energy_class_g</div></div></div>	<div><div>Marks</div><div></div></div>	
Notes	<div><div>Colour of the luminaires</div><div><div></div><div></div><div></div></div></div>		
	<div><div>Colour Temperature</div><div><div>3000 K warm white</div><div>4000 K cool white</div></div></div>		
	<div><div>Optic system</div><div><div>Microprisma</div><div>Opal diffuser</div></div></div>		
	<div><div>Connection of the luminaires</div><div><div>ON/OFF</div></div></div>		
	<div><div>Ra</div><div><div>80</div></div></div>		
<div>End caps, suspensions, supply cables, and ceiling cup for luminaires must be ordered separately. To connect into systems, please order the respective number of couplers.</div>			


Flumo60-S

<div><div><div>580</div><div>860</div><div>1140</div><div>1420</div><div>1700</div><div>1980</div><div>2260</div></div><div><div>A-A:</div><div><div><div>65</div><div>60</div></div></div><div><div>A</div><div>A</div></div></div></div>	<div><div>Assembly</div><div><div><div><div></div></div></div></div></div>	<div><div>Light distribution</div><div><div><div></div></div></div></div>
<div><div>Energy class</div><div><div>energy_class_g</div></div></div>	<div><div>Marks</div><div></div></div>	









Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF
	Ra	80
End caps, suspensions, supply cables, and ceiling cup for luminaires must be ordered separately. To connect into systems, please order the respective number of couplers.		

Flumo60-S

	Assembly	Light distribution
	 Energy class energy_class_g	 Marks









Notes	Colour of the luminaires	
	Colour Temperature	3000 K warm white 4000 K cool white
	Optic system	Microprisma Opal diffuser
	Connection of the luminaires	ON/OFF
	Ra	80
End caps, suspensions, supply cables, and ceiling cup for luminaires must be ordered separately. To connect into systems, please order the respective number of couplers.		

Flumo60-S




	<table><tr><th>Assembly</th><th>Light distribution</th></tr><tr><td></td><td></td></tr><tr><th>Energy class</th><th>Marks</th></tr><tr><td>energy_class_g</td><td></td></tr></table>		Assembly	Light distribution			Energy class	Marks	energy_class_g	
	Assembly	Light distribution								
										
	Energy class	Marks								
	energy_class_g									
Notes	Colour of the luminaires									
	Colour Temperature	3000 K warm white 4000 K cool white								
	Optic system	Microprisma Opal diffuser								
	Connection of the luminaires	ON/OFF								
	Ra	80								
End caps, suspensions, supply cables, and ceiling cup for luminaires must be ordered separately. To connect into systems, please order the respective number of couplers.										

Legend

Type of installation

	Recessed lights		Wall mounted lights
	Semi-recessed luminaire		Suspended lights
	Surface lights		Free-standing lights
	3 circuit track lights		Table lamp lights







Light distribution

	Direct luminaire
	Direct-indirect luminaire
	Indirect luminaire

Light source

	Tunable White adjusting the color temperature		RealWhite true display of white color
	RealColour true display of colors Ra≥97		StrongColour highlight one color

Marks

	Luminaire of electrical classification I (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification II (accessible conductive parts are connected to a protective cable)
	Luminaire of electrical classification III (protection against electric shock is based on double or reinforced insulation)
	European mark of conformity that indicates the conformity of the properties of the product with all the harmonized standards and regulations of the European Community that apply to it
	Luminaires are certified according to the European ENEC system
	Recommended mounting hole size

IPxy IP code indicating the degree of protection of live parts

EAC Eurasian Conformity

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

11S-501I-20GGE/840, W

Optic system

Electrical connection

Colour












Optic system

B	Microprismatic system, low UGR	L	Plain aluminium reflector
C	Clear cover	M	Matt parabolic louvre
D	Asymmetric reflector	S	SPOT - narrow angle
E	Polished parabolic louvre, high LOR	U	MEDIUM - middle angle
F	FLOOD - wide angle	W	Wide beam angle
I	Microprismatic optical system	Z	Plastic louver, low UGR
K	Opal diffuser		




Electrical connection

/BT	Luminaires controlled via Bluetooth technology	P	Sensor and electronic ballast
D	DALI dimmable	T	By switch dimmable (touch dimm)
E	Electronic ballast non-dimmable	TD	DALI or by switch (touch dimm) dimmable
M	Electronic ballast non-dimmable with 1h emergency	U	Dimmable luminaire with dimmer on the luminaire
M3	Electronic ballast non-dimmable with 3h emergency		

Colour

W	 RAL 9003	B	 RAL 9005	S	 TIGER 09/90530
1021	 RAL 1021	2000	 RAL 2000	3020	 RAL 3020
5015	 RAL 5015	6018	 RAL 6018	7016	 RAL 7016
9006	 RAL 9006	9010	 RAL 9010		

Značky typu

	Smart – Luminaire or the lighting system controlled by motion, daylight or via smart devices using Bluetooth technology
	Acoustic – Luminaire with acoustic absorption properties which reduce disturbing noise and improve the acoustics of the room
	Multiwatt – Luminaires with individually adjustable luminous flux using a special antenna or mobile application

UGR UGR – The luminaire suitable for office spaces